

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/034386 A1

(51) International Patent Classification⁷: **G11B 7/00, 7/125**

TASAKA, Shuichi [JP/JP]; 2-3-1-503, Sumiregaoka,
Takarazuka-shi, Hyogo 665-0847 (JP).

(21) International Application Number:

PCT/JP2003/013011

(74) Agent: **OKUDA, Seiji**; OKUDA & ASSOCIATES, 2nd
Floor, Kataoka Bldg., 3-6, Uchiawajimachi 1-chome,
Chuo-ku, Osaka-shi, Osaka 540-0038 (JP).

(22) International Filing Date: 9 October 2003 (09.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

| | | |
|-------------|------------------------------|----|
| 2002-297295 | 10 October 2002 (10.10.2002) | JP |
| 2002-312432 | 28 October 2002 (28.10.2002) | JP |

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD.** [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SHOJI, Mamoru** [JP/JP]; 3-13-4-805, Mozuumemachi, Sakai-shi, Osaka 591-8032 (JP). **KOISHI, Kenji** [JP/JP]; 3-56-8, Keyakidai, Sanda-shi, Hyogo 669-1321 (JP). **NAKAMURA, Atsushi** [JP/JP]; 2-7-27-1107, Satanakamachi, Moriguchi-shi, Osaka 570-0002 (JP). **ISHIDA, Takashi** [JP/JP]; 13-14, Hashimotoisoku, Yawata-shi, Kyoto 614-8331 (JP).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL DATA RECORDING METHOD

(57) **Abstract:** The optical data recording method comprising the steps of: modulating data to be recorded, to generate a plurality of recording modulation codes; and emitting a pulse-like light beam to an optical disc, so that a plurality of recording marks and spaces which have lengths corresponding to the plurality of recording modulation codes are formed on the optical disc. In the optical data recording method, at least two of the plurality of recording marks comprises: a first pulse which is disposed at a front and forms a leading edge of the recording mark, a last pulse which is disposed at a backend and forms a trailing edge of the recording mark, and a multi-pulse train which is disposed between the first pulse and the last pulse and forms a center of the recording mark. The multi-pulse train has a pulse period longer than T which represents a reference period of the recording modulation code.

BEST AVAILABLE COPY



WO 2004/034386 A1